

Vibrator Accessories – P Series Mounting Plates



Part Number	Dimensions		Suits Model	Nut Torque	
	Width	Depth		Min (N)	Max (N)
PMP25	50	25	P25	50	72
PMP40	50	25	P40	150	174
PMP60	75	40	P60	180	230

Supplied with Nyloc Nuts and Washers

Installation Guidelines for Mounting Plates		Filter Regulator Package															
<ol style="list-style-type: none"> Fully weld the plate to the wall of the hopper/bin approx. 1/3rd up from the outlet. Mount the vibrator and secure with nuts and washers. Tighten the nuts to the torque specified in the table. 																	
		<table border="1"> <thead> <tr> <th colspan="5">Filter Regulator Package</th> </tr> <tr> <th>Flow</th> <th>Port Size</th> <th>Drain</th> <th>Bracket</th> <th>Gauge</th> </tr> </thead> <tbody> <tr> <td>2940 LPM</td> <td>103 CFM</td> <td>¼ or ½</td> <td>Auto Neck Mount</td> <td>0-10 Bar</td> </tr> </tbody> </table>	Filter Regulator Package					Flow	Port Size	Drain	Bracket	Gauge	2940 LPM	103 CFM	¼ or ½	Auto Neck Mount	0-10 Bar
Filter Regulator Package																	
Flow	Port Size	Drain	Bracket	Gauge													
2940 LPM	103 CFM	¼ or ½	Auto Neck Mount	0-10 Bar													
		<p>Also Stockists of Solenoid Valves, Ball Valves, Air Fitting, Airline, Nitto Fittings & Silencers</p>															