

Available from:

**FILQUIP Pty Limited**

5/126 Compton Rd, Underwood,  
Qld 4119 Australia

Ph: +61 7 3208 3499 Fx: +61 7 3208 3449

Email: [sales@filquip.com.au](mailto:sales@filquip.com.au)

[www.filquip.com.au](http://www.filquip.com.au)

**ALMiG**  
Compressor Systems

German Quality and Innovation

Compressed Air Products

## Compressed Air Products



With a compact footprint and low noise level, ALMiG COMBI 4-in-1 compressed air stations can be located directly adjacent to the worksite. The rotary screw compressor, air tank, refrigerant dryer and dual filters are integrated into a stand-alone compressed air system.


**COMBI 8-8**

**COMBI 11-8**

**COMBI 15-8**

<b>Motor Power</b>	7.5 kW (10 hp)	11 kW (15 hp)	15 kW (20 hp)
<b>Free Air Delivery</b>	1.09 m³/min (39 cfm)	1.61 m³/min (57 cfm)	1.96 m³/min (70 cfm)
<b>Working Pressure</b>	8 bar (116 psi)	8 bar (116 psi)	8 bar (116 psi)
<b>Optional Pressures</b>	10 bar (145 psi)	10 bar (145 psi)	10 bar (145 psi)
<b>Tank Volume</b>	500 Litres	500 Litres	500 Litres
<b>Air Treatment</b>	Dryer, Pre- & Post-Filters	Dryer, Pre- & Post-Filters	Dryer, Pre- & Post-Filters
<b>Noise Level</b>	63 dB(A)	63 dB(A)	67 dB(A)
<b>Warranty</b>	5 Years (conditions apply)	5 Years (conditions apply)	5 Years (conditions apply)
<b>Product Code</b>	AL COMBI 8-8	AL COMBI 11-8	AL COMBI 15-8


**COMBI 18-8**

**COMBI 22-8**

<b>Motor Power</b>	18.5 kW (25 hp)	22 kW (30 hp)
<b>Free Air Delivery</b>	2.75 m³/min (98 cfm)	3.24 m³/min (115 cfm)
<b>Working Pressure</b>	8 bar (116 psi)	8 bar (116 psi)
<b>Optional Pressures</b>	10 bar (145 psi)	10 bar (145 psi)
<b>Tank Volume</b>	500 Litres	500 Litres
<b>Air Treatment</b>	Dryer, Pre- & Post-Filters	Dryer, Pre- & Post-Filters
<b>Noise Level</b>	71 dB(A)	71 dB(A)
<b>Warranty</b>	5 Years (conditions apply)	5 Years (conditions apply)
<b>Product Code</b>	AL COMBI 18-8	AL COMBI 22-8

ALMiG COMBI SC 4-in-1 compressed air stations can reduce your electricity costs up to 35% by automatically varying their output to match the fluctuating air demand of most applications. These compact, quiet and energy-efficient compressed air systems are supplied ready-to-run.

**COMBI SC11-8****COMBI SC22-8**

<b>Motor Power</b>	11 kW (15 hp)	22 kW (30 hp)
<b>Free Air Delivery</b>	0.62-1.50 m³/min (22-53 cfm)	1.21-3.09 m³/min (43-110 cfm)
<b>Working Pressure</b>	8 bar (116 psi)	8 bar (116 psi)
<b>Pressure Range</b>	5-13 bar, Stepless	5-13 bar, Stepless
<b>Tank Volume</b>	500 Litres	500 Litres
<b>Air Treatment</b>	Dryer, Pre- & Post-Filters	Dryer, Pre- & Post-Filters
<b>Noise Level</b>	60 - 63 dB(A)	66 - 71 dB(A)
<b>Warranty</b>	5 Years (conditions apply)	5 Years (conditions apply)
<b>Product Code</b>	AL COMBI SC11-8	AL COMBI SC22-8

Available from:  
**FILQUIP Pty Limited**

5/126 Compton Rd  
Underwood Qld 4119  
Australia  
Phone: +61 7 3208 3499  
Fax: +61 7 3208 3449  
Email: [sales@filquip.com.au](mailto:sales@filquip.com.au)  
[www.filquip.com.au](http://www.filquip.com.au)