



Available from:

FILQUIP Pty Limited

5/126 Compton Rd, Underwood, Qld 4119 Australia Ph: +61 7 3208 3499 Fx: +61 7 3208 3449 Email: sales@filquip.com.au www.filquip.com.au

SEPCOM®Animal Waste Separator











MULTIPLE PATENTS PENDING






Specially formulated for this specific type of slurry, SEPCOM ® is simple, reliable, efficient and economical.

Re-using slurry offers enormous advantages in terms of transportation, storage, cleanliness and energy saving.

Separating the solids in slurry from the liquid is THE ANSWER TO THE URGENT PROBLEM OF **NITRATES.**



LIQUID PHASE

Easy to spread, mix, and pump

Minimum residual sedimentation or incrustation

Can be used for washing out sheds

Excellent for ferti-irrigation



Flushing



Ferti-irrigation

SOLID PHASE

Shovelable, easy to store and convey

Can be used as bedding for animals

Excellent as soil ammendant The product can be marketed Odourless, non-percolating product



Shovelable, easy to transport and store even in enclosed spaces



Ideal cattle bedding




The product can be marketed











Casing extension (This accessory increases capacity)




Diaphragm outlet: self-adjusting back pressure





Feeder: compensating buffer (obligatory accessory)














RANGE	A mm	B mm	C mm	Power consumption kW	Weight kg	Max. capacity m³/h*
SEPCOM® 045	975	1.622	2.767	4	490	45
SEPCOM® 065	975	1.922	2.767	5.5	580	65

Body in carbon steel or stainless steel. Screw in self-cleaning technopolymer. Sieve in stainless steel.





SPECO® - Division of WAM S.p.A. Via Cavour, 338 I - 41030 Ponte Motta Cavezzo (MO) - ITALY

Tel: +39 0535 61 81 11 Fax: +39 0535 61 82 26 info@wamgroup.com www.wamgroup.com

Available from: FILQUIP Pty Limited

www.filquip.com.au

5/126 Compton Rd, Underwood, Qld 4119 Australia Ph: +61 7 3208 3499 Fx: +61 7 3208 3449 Email: sales@filquip.com.au

^{*} Capacity may vary depending on the type of input material, working conditions, and maintenance of the machine.